



Features

- 4-inch/100mm Micro Ceramic Composite (MCC) aluminum diaphragm woofer
- 3/4-inch/19mm Micro Ceramic Composite (MCC) aluminum diaphragm tweeter
- IP67 rating that certifies protection against dust, and strong water jets and waves
- 4-Ohm or 70V operation via integrated transformer with selectable power taps up to 60W
- Sliding clamp assembly allows you to adjust the center of gravity

Specifications

Low Frequency Drive Size and Material	4" Micro Ceramic Composite (MCC) Aluminum Cone Woofer
High Frequency Driver Size and Material	0.75" Micro Ceramic Composite (MCC) Aluminum Dome Tweeter
Recommended Amplifier Power	60W RMS; 100W RMS with High Pass Filter @100Hz
70V Transformer Taps	7.5W, 15W, 30W, 60W
Voltage	70V
Rated Impedance	4 Ohm in Bypass mode
Loudspeaker Sensitivity	83dB (2.83V @1M) in Bypass mode
Frequency Response	100Hz – 20kHz @-3dB
Crossover Frequency	5.5kHz
Coverage Angle (Dispersion)	70 degrees horizontal; 70 degrees vertical
Dimension Details	23.3cm (9.2") speaker body length 13.2cm (5.2") speaker body diameter 28.5cm (11.3") height with clamp and base 59cm (23.2") height with clamp and spike
Dimension Totals	Length 23.3cm (9.2") Width 16.4cm (6.5") Height 29.5cm (11.3")
Weight	Speaker and clamp assembly – 4.5kg (9.9 lbs)

Revel L41XC

