







The MMD tweeter and waveguide deliver

# A HERITAGE OF EXCELLENCE.

The road to Primus stretches back more than 30 years — a road lined with literally dozens of audio milestones.

With innovative technologies, materials and manufacturing techniques, Infinity has advanced the science of sound year after year.

Primus Series speakers benefit from every Infinity innovation that has ever come before. They also embody everything we've learned about making captivating sound affordable.



Infinity's flagship system, the Prelude MTS.

# ONE BREAKTHROUGH DESERVES ANOTHER.

Infinity's critically acclaimed
Prelude" MTS introduced a
revolutionary transducer technology
that dramatically reduced
distortion to produce a more
natural, detailed sound.

That patented advance led directly to Infinity's new Metal Matrix Diaphragm (MMD™) technology. Used throughout the Primus Series, MMD transducers deliver crystalclear, distortion-free sound from dynamic digital sources, even at high listening levels.

# THE MMD™ DIFFERENCE.

Unlike the paper, polypropylene or Kevlar® cones found in similarly priced speakers, MMD cones consist of a stiff aluminum core, anodized on both sides for increased strength and rigidity.

The result is extremely fast, extremely accurate transducers, producing a distinctly cleaner, more realistic sound.

#### Music? Or Movies? Or Both?

From unobtrusive bookshelf music systems to dazzlingly powerful home theaters, there's a Primus system that's right for every purpose and room in your home. Infinity also offers three powered subwoofers to perfectly complement your Primus speakers. A recommended addition to any system, these three subs allow you to duplicate the cinematic experience at home.



Add the PS-8, PS-10 or PS-12 powered subwoofer for incredible music and hom

STIFFER, LIGHTER, STRONGER. THE MMD CONE IS SUPERIOR TO OTHER COMMONLY USED MATERIALS IN VIRTUALLY EVERY PERFORMANCE CHARACTERISTIC.



# PERFORMANCE THAT'S PURE INFINITY.

Sound that commands your focused, undivided attention, transforming the act of listening from a passive pursuit to an engaging endeavor. That's the heritage of Infinity — and the promise of Primus.



Five-way binding posts provide secure connection and easy setup.

#### A New Benchmark for Value.

Primus is designed to deliver a listening experience unlike anything in its price class, but Infinity confidently encourages you to reach your own conclusion.



PRIMUS FROM INFINITY. PREPARE To Raise Your Expectations.

a new level of clarity and realism. Let your favorite movies and music capture you as never before. This is where Infinity begins, and it's well within your reach.









	O
ECIFICATIONS	Primus 140
quency Range (±3dB)	100Hz — 20,000Hz
ommended	10 — 100 watts

3000Hz; 24dB/octave

4" (100mm) MMD,™ magnetically shielded

3/4" (19mm) MMD, magnetically shielded

7 lb (3.2kg)

9-5/8" x 5-15/16" x 6-13/16" (245mm x 150mm x 173mm)

86dB

8 ohms

Amp Power Range Sensitivity (2.83V @ 1 meter)

SP

Freq

**Nominal Impedance Crossover Frequency** 

Low-Frequency Driver(s)

Mid-Frequency Driver

High-Frequency Driver

Dimensions (H x W x D) (with grille)

Weight

Ö	9
D : 1F0	D: 100

10 - 100 watts

3300Hz; 24dB/octave

5-1/4" (130mm) MMD,™ magnetically shielded

3/4" (19mm) MMD, magnetically shielded

13.5 lb (6kg)

12-3/4" x 7-3/8" x 10-1/2" (322mm x 187mm x 267mm)

88dB

Ö	9
Primus 150	Primus 160
58Hz — 20,000Hz	49Hz — 20,000Hz

9
Primus 160
49Hz — 20,000Hz
10 — 150 watts

90dB

8 ohms

3000Hz; 24dB/octave

6-1/2" (165mm) MMD," magnetically shielded

3/4" (19mm) MMD, magnetically shielded

16.1 lb (7.3kg)

14-1/2" x 8-1/4" x 11" (370mm x 208mm x 280mm)



Primus 360	Primus C25
38Hz — 20,000Hz	80Hz — 20,000Hz
10 — 200 watts	10 — 150 watts
93dB	90dB

10 — 150 watts	10 — 200 watts	10 — 150 watts
92dB	93dB	90dB
8 ohms	8 ohms	8 ohms
2500Hz; 24dB/octave	350Hz, 3300Hz; 24dB/octave	3000Hz; 24dB/octave
Dual 5-1/4" (130mm) MMD,™ magnetically shielded	Dual 6-1/2" (165mm) MMD,™ magnetically shielded	Dual 5-1/4" (130mm) MMD," magnetically shielded
N/A	4" (100mm) MMD, magnetically shielded	N/A
3/4" (19mm) MMD, magnetically shielded	3/4" (19mm) MMD, magnetically shielded	3/4" (19mm) MMD, magnetically shielded
35-1/2" x 7-3/8" x 11-3/4" (900mm x 187mm x 300mm)	39" x 8-1/4" x 13" (990mm x 208mm x 330mm)	7-5/8" x 17-1/2" x 9-5/8" (187mm x 444mm x 245mm)
35.3 lb (16kg)	48.5 lb (22kg)	17.6 lb (8kg)



### Primus Theater Pack

	Satellites	Center Channel
Frequency Range (±3dB)	100Hz — 20,000Hz	100Hz — 20,000Hz
Recommended Amp Power Range	10 — 100 watts	10 — 100 watts
Sensitivity (2.83V @ 1 meter)	86dB	87dB
Nominal Impedance	8 ohms	8 ohms
Crossover Frequency	3000Hz; 24dB/octave	3000Hz; 24dB/octave
Low-Frequency Driver(s)	4" (100mm) MMD,™ magnetically shielded	Dual 4" (100mm) MMD,™ magnetically shielded
High-Frequency Driver	3/4" (19mm) MMD, magnetically shielded	3/4" (19mm) MMD, magnetically shielded
Dimensions (H x W x D) (with grille)	9-5/8" x 5-15/16" x 6-13/16" (245mm x 150mm x 173mm)	5-5/16" x 14-1/4" x 6-13/16" (150mm x 363mm x 173mm)
Weight	7 lb (3.2kg)	10 lb (4.5kg)

# PS Series Powered Subwoofers ADD AN INFINITY SUB TO MAXIMIZE BASS IMPACT AND REALISM.



38 lb (17.3kg)

45 lb (20.5kg)



Frequency Range

Maximum Amp Output

Crossover Frequency

Driver

Dimensions (H x W x D) Weight

33 lb (15kg)