



SPECIFICATIONS

G50

G100

G200

High Frequency Transducer	14mm	14mm	1"
Low Frequency Transducer	5"	5"	6 1/2"
Crossover Frequency	3 kHz	3 kHz	3 kHz
Frequency Response (-6 dB)	80 Hz-20 kHz	70 Hz-20 kHz	55 Hz-20 kHz
Sensitivity (1 Watt/ 1 meter)	86 dB	87 dB	88 dB
Nominal Impedance	6 Ohms	6 Ohms	6 Ohms
Power Handling Range	10-50 watts	10-50 watts	10-60 watts
External Dimensions (H X W X D) (millimeters)	12-3/16" x 7-1/8" x 8-3/4"	12-3/16" x 7-1/8" x 8-3/4"	15" x 9-1/4" x 8-13/16"
Weight (each)	310 x 181 x 222	310 x 181 x 222	381 x 235 x 224
	8 lbs /3.6 kg	8 lbs /3.6 kg	12.1 lbs /5.5 kg



SPECIFICATIONS

G300

G400

G500

High Frequency Transducer	1"	14mm	1"
Midrange Transducer	5"	5"	5"
Low Frequency Transducer	8"	10"	(2) 8"
Crossover Frequency	600 Hz/3.5 kHz	800 Hz/4.5 kHz	600 Hz/3.5 kHz
Frequency Response (-6 dB)	50 Hz-20 kHz	35 Hz-20 kHz	42 Hz-20 kHz
Sensitivity (1 Watt/ 1 meter)	89 dB	91 dB	91 dB
Nominal Impedance	8 Ohms	8 Ohms	6 Ohms
Power Handling Range	10-80 watts	10-150 watts	10-120 watts
External Dimensions (H x W x D) (millimeters)	21-1/4" x 10-3/4" x 10-1/2"	34-1/2" h" x 13" x 11-3/4"	37-7/8" x 10-5/8" x 12-3/4"
Weight (each)	540 x 272 x 267	876 x 330 x 298	960 x 270 x 323
	20 lbs/9.1 kg	36 Lbs/16.3 kg	36.3 lbs/16.5 kg

JBL continually strives to improve its products. New materials, production methods and design refinements are introduced into existing models without notice as a routine expression of our design philosophy. For this reason, JBL loudspeakers may differ in some respect from their published specifications and descriptions, but will always equal or exceed the original specifications unless otherwise stated. JBL is a registered trademark and Signature Sound is a trademark of JBL Incorporated. ©1993 JBL Incorporated.



JBL Consumer Products, Inc.
240 Crossways Park West,
Woodbury, NY 11797
8500 Balboa Blvd.
Northridge, CA 91329
1 800 336 4JBL