

reference series

subwoofers



car audio

INFINITY® REFERENCE SUBWOOFERS

Looking for a more moving audio experience? Take Infinity® car audio for a ride. Innovative materials and breakthrough engineering have always put Infinity products out in front of the competition. So expect extreme output from these subwoofers, but be prepared for accuracy and detail that may surprise you. Infinity Reference Series subwoofers deliver serious low end while taking up less space, thanks to their proprietary reduced-frame geometry.





LARGE-ROLL RUBBER SURROUNDS

This material provides optimal cone-edge suspension and absorbs distortions that may travel up the cone edge. The benefit is an audible reduction in distortion.

PROGRESSIVE SPIDER

Each Reference subwoofer features a progressive spider, applying progressively more force as the cone travel approaches its limit. The result is a subwoofer in better control when pushed to extreme excursions, delivering more bass, free from distortion and breakup.

PROPRIETARY TINSEL-LEAD SUPPORT

This prevents tinsel-lead slap and ensures that the leads stay attached to the cone, even at the woofer's excursion limits.

PROPRIETARY FRAME

The unique frame design used on all Reference subwoofers provides a decrease in mounting depth, while maximizing woofer excursion. If you want to add subwoofers in a pickup or in a confined space, these subs are the ideal solution.

850w

8" (200mm) Subwoofer

Polypropylene woofer cone
Proprietary reduced-depth frame
Single 4-ohm voice coil
Sensitivity: 91dB
Frequency response: 30Hz – 400Hz
Power handling, RMS: 200 watts
Power handling, peak: 800 watts

1050w

10" (250mm) Subwoofer

Polypropylene woofer cone
Proprietary reduced-depth frame
Single 4-ohm voice coil
Sensitivity: 91dB
Frequency response: 25Hz – 400Hz
Power handling, RMS: 250 watts
Power handling, peak: 1000 watts

1052w

10" (250mm) Dual-Voice-Coil Subwoofer

Polypropylene woofer cone
Proprietary reduced-depth frame
Dual 4-ohm voice coils
Sensitivity: 91dB
Frequency response: 25Hz – 400Hz
Power handling, RMS: 250 watts
Power handling, peak: 1000 watts

1250w

12" (300mm) Subwoofer

Polypropylene woofer cone
Proprietary reduced-depth frame
Single 4-ohm voice coil
Sensitivity: 93dB
Frequency response: 23Hz – 400Hz
Power handling, RMS: 300 watts
Power handling, peak: 1000 watts

1252w

12" (300mm) Dual-Voice-Coil Subwoofer

Polypropylene woofer cone
Proprietary reduced-depth frame
Dual 4-ohm voice coils
Sensitivity: 93dB
Frequency response: 23Hz – 400Hz
Power handling, RMS: 300 watts
Power handling, peak: 1000 watts



250 Crossways Park Drive, Woodbury, NY 11797 USA
516.674.4INF (4463) Fax 516.682.3556
www.infinitysystems.com

© A Harman International Company

© 2008 Harman International Industries, Incorporated.
All rights reserved. Part No. INFREFSUBPI3-08

Features, specifications and appearance are subject to change without notice. Designed, edited and digitally produced by the Harman Consumer Group Marketing & Design Center, Woodbury, NY.

Infinity is a trademark of Harman International Industries, Incorporated, registered in the United States and/or other countries.