



JBL® CONTROL® SERIES

JBL Control NOW™ and JBL Control NOW AW loudspeakers

Loud, clear, stunningly realistic audio reproduction for public spaces and private homes has been the JBL® stock-in-trade for more than 60 years. But in all those years, there has never been anything even remotely like JBL Control NOW™ loudspeakers or the all-weather JBL Control NOW AW speakers. Advanced JBL technologies have been seamlessly engineered into a unique arched enclosure that makes these speakers perhaps the most flexible ever developed. Individually, or in a circular or semicircular array of up to four speakers, there's virtually no place where JBL Control NOW speakers cannot go, and there are more than a few places where only they can fit.

SPECIFICATIONS

Maximum recommended amplifier power*:	150W
Power handling:	50W continuous/300W peak
Frequency response:	80Hz – 30kHz (-6dB)
Nominal impedance:	8 ohms
Sensitivity:	90dB @ 1 watt/1 meter
Crossover point:	2kHz
Crossover slope:	18dB/octave (low-frequency driver); 36dB/octave (high-frequency driver)
Low-frequency drivers:	Dual 100mm (4") PolyPlas™, shielded
High-frequency driver:	19mm (3/4") titanium-laminate, shielded

Finishes:



* The maximum recommended amplifier power rating will ensure proper system headroom to allow for occasional peaks. We do not recommend sustained operation at these maximum power levels.

JBL CONTROL SERIES

JBL Control NOW and JBL Control NOW AW loudspeakers

HIGHLIGHTS

90 degrees of pure ingenuity

One speaker, dozens of mounting possibilities – perhaps the most flexible speaker ever developed

Evenly distributed sound with minimal distortion in any listening environment

Optional pole-mount bracket kit for hanging a four-speaker array

Inclusive multi-unit wiring adapter eliminates impedance restrictions

KEY SPECIFICATIONS

- Finish: Black (indoor) or White (all-weather*)
- Arrays of two, three and four speakers can be mounted virtually anywhere and can be configured for either single-channel or single-point stereo use
- Use them in traditional stereo setups, for home theatres or for whole-house-music and background-music systems
- Patented Bi-Radial® horn delivers smooth, wide and uniform high-frequency response even in challenging placement such as corner mounting and multi-unit configurations
- Low-frequency drivers: dual 100mm (4") PolyPlas, shielded
- High-frequency driver: 19mm (3/4") titanium-laminate, shielded
- Frequency response (–6dB): 80Hz – 30kHz

* Please note that while the JBL Control NOW AW loudspeaker is an all-weather outdoor speaker, it is not waterproof. It should be sheltered from direct exposure to ice, snow and sustained moisture.

MOUNTING OPTIONS

- Mounting options for single speakers and multispeaker arrays are literally too numerous to list in detail. But just to get you thinking in the right direction, here are a few possibilities.

Option 1: On a bookshelf either vertically or horizontally placed



Option 2: In a corner between walls, or between a wall and ceiling (using inclusive bracket)




Option 3: On a wall, vertically, horizontally or in a two-speaker array (using inclusive bracket)



Option 4: As a three-speaker horizontal array, mounted on a wall corner (using inclusive bracket)



Option 5: On a floor stand using included floor stand adapter, compatible with a multitude of third-party stands



Option 6: As a four-speaker array (using the optional pole-mount bracket and standard ceiling fan hardware)



HARMAN

HARMAN Consumer, Inc.
8500 Balboa Boulevard, Northridge, CA 91329 USA

© 2012 HARMAN International Industries, Incorporated. All rights reserved. JBL, Bi-Radial and Control are trademarks of HARMAN International Industries, Incorporated, registered in the United States and/or other countries. JBL Control NOW and PolyPlas are trademarks of HARMAN International Industries, Incorporated.

Features, specifications and appearance are subject to change without notice.

www.jbl.com