

EON718S

Powered 18-inch PA Subwoofer

JBL

PROFESSIONAL
by HARMAN

SPEC SHEET



OVERVIEW

The **JBL EON718S** 18-inch powered subwoofer, part of JBL's new EON700 Series of powered loudspeakers, brings advanced DSP and control to portable PA systems for live sound and installed applications, with class-leading volume and clarity and comprehensive features that make setup and operation a breeze.



REAR PANEL CONNECTIONS

PRODUCT HIGHLIGHTS

- 18-inch woofer
- Power:** 1,500W Peak / 750W RMS
- Frequency response:** 31Hz - 150Hz (-10)
40Hz - 120Hz (-3)
- Max SPL:** 131 dB
- Audio I/Os:** 2 XLR Combo, 2 XLR loop-thru
- Advanced dbx DSP:** Parametric EQ, polarity inversion, speaker delay
- Built-in 2-channel digital mixer
- Color backlit LCD screen provides easy access to functions
- Universal JBL Pro Connect app control
- Durable birch plywood cabinet with duraflex paint and metal grille
- Two ergonomic handles simplify transport
- Built-in threaded pole mount.
- Built to stack for storage and use in cardioid mode.
- Net Weight:** 35.5kg (78.26 in.)

EON718S

Powered 18-inch PA Subwoofer



SPEC SHEET

SPECIFICATIONS ■

System Type	18IN Powered Subwoofer	Cooling	Passive
Woofers Model	718G	LED Indicators	1 Power LED, 1 System Limit, 1 Front LED
Woofers Size	18"	Input Impedance	50k/100k un-balanced/balanced
Woofers Magnet	Ferrite	Input Gain	-∞ to +36db
Woofers Voice Coil	3"	I/O	2 XLR Combo 2 XLR M Thru
Transducer Impedance	4 ohm rated	Cabinet	18mm Duraflex-coated Birch Plywood
Max SPL	131dB @1m/2Pi	Grille	16GA perforated steel with acoustically transparent black cloth backing
Freq Range -10	31Hz - 150Hz	Suspension/Mount	1 M20 Threaded Polecup
Freq Range -3	40Hz -120Hz	Handles	2
Hor Dispersion	Omni	Net Weight	35.5kg (78.26 in.)
Vert Dispersion	Omni	Gross Weight	42.5kg (93.70 in.)
Crossover Frequency	80, 100, 120Hz selectable	Product Dims	LxWxH 609 x 637 x 674 mm (23.98 x 25.08 x 26.54 in.)
Power Rating	1500W Peak Power 1500Wpk/500Wrms/170Wcont.	Shipping Dims	LxWxH 743 x 713 x 722 mm (29.25 x 28.07 x 28.43 in.)
AC Power Input	100V-120V or 220V-240V		


EON718S

Powered 18-inch PA Subwoofer



SPEC SHEET

FREQUENCY RESPONSE ■



PRODUCT DIMENSIONS ■

