

LS360C IN-CEILING HOME THEATER LOUDSPEAKER.

You can tell at a glance that this is no ordinary in-ceiling loudspeaker. With a patent-pending flat-panel mid-bass transducer, a pure-titanium tweeter, dual midranges and a built-in back box, the JBL® LS360C has virtually nothing in common with conventional in-ceiling designs. O.K., it's round, but that's where comparisons end.

EXPERIENCE FULL-SPECTRUM HOME THEATER EXCITEMENT ON A WHOLE NEW LEVEL.

The LS360C employs advanced JBL technologies and materials in a unique three-way configuration to deliver the kind of high-output, high-impact sound today's home theater installations demand – and for which JBL is famous. Now all the hyperrealistic, multichannel excitement you yearn to experience can come from ceiling speakers alone, freeing up a few cubic feet of living space in the bargain.

You'll hear clearer, more distinct movie dialogue, because the LS360C's flat-panel driver radiates mid-bass frequencies more evenly. The high frequencies are equally clean and brilliant, thanks to the pure-titanium-dome tweeter with its integral EOS waveguide and independent level controls. And bass response is smoother, thanks to the back box and the boundary compensation adjustment.

Easy to install. Nearly out of sight. Thrilling to hear. Which part of "everything you want in a home theater system" doesn't that cover?



THE LS360C IN-CEILING HOME THEATER SPEAKER: TRUE JBL PERFORMANCE REACHES NEW HEIGHTS. FROM THE EXPERTS AT JBL.

LS360C

In-Ceiling Home Theater Speaker

Frequency Response ($\pm 3\text{dB}$)	80Hz – 20kHz
Recommended Amplifier Power Range*	10 – 200 Watts
Sensitivity (2.83V/1m)	85dB
Nominal Impedance	8 Ohms
Crossover Frequency	700Hz; 2,000Hz; 24dB/octave
Low-Frequency Driver	7-3/4" x 3-3/8" (197mm x 85mm)
Midrange Drivers	Dual 3" (75mm)
High-Frequency Driver	1" (25mm) Pure titanium
External Diameter	12-3/4" (323mm)
Mounting Cutout Diameter	11-3/8" (289mm)
Mounting Depth	5-5/8" (142mm)
Weight per Speaker	8 lb (3.6kg)
Features	Paintable frames and grilles; easy-to-install, integrated dog-ear brackets



EASY TO INSTALL.

The LS360C features mounting clamps that swing out to securely grip your wall from the inside. Because it need not be mounted to a stud, the speaker can be placed for optimal sonic performance and installation ease.



ROUGH-IN FRAMES.

Optional RIF10C rough-in frame is available for use in new-construction installations before drywall is installed.

JBL

PRO SOUND COMES HOME™

Harman Consumer Group, Inc.
250 Crossways Park Drive, Woodbury, NY 11797
8500 Balboa Boulevard, Northridge, CA 91329
516.255.4JBL (4525) www.jbl.com

©2007 Harman International Industries, Incorporated.
All rights reserved.

Part No. LS360CPI8/07 Printed in USA 8/07

H A Harman International Company

Features, specifications and appearance are subject to change without notice.

JBL is a trademark of Harman International Industries, Incorporated, registered in the United States and/or other countries. Pro Sound Comes Home is a trademark of Harman International Industries, Incorporated.

Designed, edited and digitally produced by the Harman Consumer Group Marketing & Design Center, Woodbury, NY.

* The recommended amplifier power range rating will ensure proper system headroom to allow for occasional peaks. We do not recommend sustained operation at these maximum power levels.