

240 Ti

Three-way system supplied in mirror imaged pairs, and designed for optimum performance when free-standing away from walls and corners. Low frequency driver is precise height from floor to give best balanced bass response. Features 1 inch HF driver, 5 inch mid-range, 14 inch LF driver, 2-position switch level controls (fixed attenuators introduce no distortion) for mid-range and HF drivers, 5-way gold binding posts, floating grilles, and oiled teak finish.

Specifications

Maximum Recommended Amplifier Power	300 watts per channel
Nominal Impedance	8 ohms
Crossover Frequencies	900 Hz, 4 kHz
Sensitivity SPL, 2.83 V at 1 m	89 dB

LF Loudspeaker

Nominal Diameter	14 in (360 mm)
Voice Coil	4 in (102 mm) edge-wound copper
Diaphragm Material	aquaplas laminate
Magnetic Assembly WT	18½ lb (8.5 kg)

Mid Range Loudspeaker

Nominal Diameter	5 in (130 mm)
Voice Coil	¾ in (22 mm) copper
Diaphragm Material	filled polypropylene
Magnetic Assembly WT	1½ lb (0.74 kg)

High Frequency Dome Radiator

Nominal Diameter	1 in (25 mm)
Voice Coil	1 in aluminum
Diaphragm Material	titanium
Magnetic Assembly WT	2 lb (0.9 kg)
General Dimensions	36½ in x 18 in x 12 in 930 mm x 457 mm x 305 mm
Weight	85 lb (38.6 kg)

